

SANDING MACHINE

BACKGROUND OF THE INVENTION

[0001] The invention concerns a sanding machine particularly suitable for being used in the surface processing of panels, doors, furniture doors and similar parts.

[0002] This type of processing is generally carried out on raw or painted wood-based materials, but in different applications it can be adopted also for different materials, like plastic or metal, to work on corners or to remove the residues of previous processing.

[0003] For this purpose automated sanding machines are known, in which appropriate abrasive elements with suitable grain are placed in contact with the surface of the piece to be sanded.

[0004] The abrasive elements are generally constituted by abrasive paper strips closed to form a ring and rotating on a pair of pulleys.

[0005] A particular type of machines normally used for sanding low relief surfaces involves the use of abrasive brushes comprising a plurality of abrasive tapes, usually interchangeable, applied to the outer surface of a rotating roller.

[0006] During operation these brushes are placed in contact with the piece to be sanded, which is set in motion by a conveyor belt on which it is fixed.

[0007] The adhesion of the piece to the conveyor belt is guaranteed by the action of suitable pressing elements that press the piece, as well as by the holding effect obtained by means of a suction unit positioned on the surface of the conveyor belt.

[0008] The piece to be sanded is set in motion by the conveyor belt substantially in one direction only with respect to the abrasive brushes that, being usually positioned over the conveyor belt, determine the sanding of one side only of the piece to be sanded, usually the visible upper surface.

[0009] Obviously, to carry out a complete sanding of all the sides of the piece, including the edges, it is necessary to carry out successive processing steps,

including coordinated movements of the abrasive brushes along different axes, or the rotation of the piece so as to position the sides to be sanded in contact with the brushes.

[0010] In different applications, to sand the lateral profiles of the piece the machine is provided with a further sanding unit, where the abrasive brushes of the type described above are arranged vertically, so that they can be placed in contact with the side edge of the piece.

[0011] A first drawback of these techniques is represented by the fact that the complete sanding of the piece requires several processing cycles.

[0012] Another drawback of these techniques is constituted by the fact that the pressure exerted by the abrasive brushes during their rotation may affect the quality of the processing in small pieces, in fact it is difficult for the pressing element to keep the piece adherent to the conveyor belt, due to the dimensions of the brushes themselves.

SUMMARY OF THE INVENTION

[0013] The aim of this invention is to overcome the drawbacks described above. One of the main aims of the invention is to manufacture a sanding machine with which a piece can be sanded with a single processing cycle.

[0014] Another aim of the invention is to manufacture a sanding machine that is capable of sanding a piece ensuring a higher quality compared to the equivalent machines of the known types.

[0015] A further aim of the invention is to manufacture a sanding machine requiring simplified maintenance operations compared to machines of the known types.

[0016] The aims described above have been achieved through the implementation of a sanding machine that, according to the contents of the main claim, is of the type comprising a support structure for the piece to be processed and a sanding unit for sanding said piece, wherein said sanding unit comprises a frame supporting:

- **[0017]** at least one winding element cooperating with kinematic means suitable for setting it in motion according to a closed-ring configuration on a plane that is substantially parallel to the plane defined by said support structure;

- **[0018]** a plurality of abrasive elements combined with said winding element, positioned spaced from one another and provided with at least one abrasive surface suitable for coming in contact with said piece during the movement of said winding element.

[0019] According to a favourite application of the invention, the winding element is constituted by a closed belt wound between two pulleys, one of which is motor driven.

[0020] Each abrasive element is constituted by a laminar abrasive element connected with the belt by means of a shaft positioned substantially perpendicular to the plane defined by the support structure.

[0021] To advantage, along their trajectory the abrasive elements sequentially involve the side edges of the piece and its visible upper surface, thus carrying out the complete sanding of the piece.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] The aims and advantages mentioned above will be better highlighted by the description of some among many possible applications of the invention in question, with reference to the enclosed drawings, wherein:

- **[0023]** FIG. 1 is an axonometric view of the sanding machine object of the invention;

- **[0024]** FIG. 2 shows a partial cross-section of FIG. 1;

- **[0025]** FIG. 3 is a side view of FIG. 1;

- **[0026]** FIGs. from 4 to 6 are schematic top views of the machine object of the invention in different piece processing phases;

- **[0027]** FIG. 7 shows a cross-section of an enlarged detail of FIG. 1;
- **[0028]** FIG. 8 is an axonometric view of a detail of an abrasive element;
- **[0029]** FIG. 9 is an axonometric view of a detail of FIG. 7;
- **[0030]** FIGs. from **10** to **12** show a schematic top view of a variant of the machine object of the invention in different piece processing phases;
- **[0031]** FIG. 13 is a schematic top view of another variant of the invention;
- **[0032]** FIG. 14 is an axonometric view with a partial cross section of a further variant of the invention;
- **[0033]** FIG. 15 shows a variant of FIG. 9.

DESCRIPTION OF THE INVENTION

[0034] The sanding machine object of the invention is shown in FIG. 1, where it is indicated as a whole by **1**.

[0035] It substantially comprises a support structure **2** for the piece **3** to be worked and a sanding unit, indicated as a whole by **4**, for sanding the piece **3**.

[0036] In the application of FIG. 1 the support structure **2** is movable with respect to the sanding unit **4** and substantially comprises a conveyor belt **5** wound to form a closed ring between a pair of rotating cylinders **6**, **7**.

[0037] In different applications the relative movement between the sanding unit **4** and the support structure **2** can be obtained, for example, by moving the sanding unit **4** only.

[0038] According to the invention, the sanding unit **4** comprises a frame **40** supporting a winding element **8**, as can be seen in greater detail in FIG. 2, cooperating with Kinematic means, indicated as a whole by **9**, and a plurality of abrasive elements **10**, combined with the winding element **8** and arranged spaced from one another along the development of the winding element **8** itself.

[0039] In particular, the winding element **8** assumes a closed ring configuration on a plane $\pi 1$ substantially parallel to the plane $\pi 2$ defined by the support structure **2**.

[0040] For convenience's sake said planes $\pi 1$ and $\pi 2$ are positioned horizontally, but it is clear that in different applications they can have any position, even inclined.

[0041] As to the winding element **8**, it is constituted by a belt closed to form a ring and cooperating, as already said, with the kinematic means **9** that set it rotating on plane $\pi 1$.

[0042] The kinematic means **9** are constituted by two pulleys **11**, **12**, between which the winding element **8** is wound and by motorization means, indicated as a whole by **13**, mechanically connected with one of said pulleys, in the case represented in the figure with pulley **12**, to set it rotating.

[0043] Each one of the abrasive elements **10**, as shown in FIG. 7, is constituted by a laminar abrasive element **14** connected with the winding element **8** by means of a shaft **15** arranged substantially perpendicular to the support structure **2**, where the piece to be processed **3** is positioned.

[0044] The laminar abrasive element **14**, as shown in the detail of FIG. 8, is preferably constituted by abrasive strips of the known type, comprising a piece of abrasive paper **16**, on which a series of fringes is obtained.

[0045] The abrasive paper **16** is positioned at the side of a series of fibrous element **17** that, owing to their intrinsic elasticity, determine the flexibility of the laminar abrasive element **14** itself.

[0046] As shown in the figures, and in particular in the top views of the FIGs. from **4** to **6**, each laminar abrasive element **14** is positioned inclined with respect to the advance directions of the winding element **8**, indicated by the arrows **18** and **19**, with respect to the two main sides **20**, **21** on which the winding element **8** itself is wound.

[0047] This inclination, in fact, ensures the soft aggression of the corners of the piece **3** with which the laminar abrasive elements come in contact.

[0048] The laminar abrasive element **14** clearly has the abrasive paper **16** positioned at the front and the fibrous elements **17** positioned at the rear with respect to the advance directions of the winding element **8**.

[0049] To allow each laminar abrasive element **14** to be arranged in an inclined position, the shaft **15** is provided with articulation means, indicated as a whole by **22**, that make it possible to define, as we shall see later on, suitable and different inclined positions of the laminar abrasive element **14**.

[0050] The articulation means **22** can be carried out according to known techniques commonly used in the mechanical sector.

[0051] To facilitate maintenance operations and the replacement of the laminar abrasive elements **14**, the same are advantageously joined to their respective support shaft **15** so that they can be removed, thus ensuring easy and quick replacement.

[0052] This is highlighted in FIG. 9, where it can be observed that the laminar abrasive element **14** is removably constrained to the support shaft **15** through holding means, indicated as a whole by **23**, constituted by a movable plate **24** positioned against the laminar abrasive element **14** through the operation of a pawl **25**.

[0053] To facilitate the guided movement of the abrasive elements **10** on the frame **40** guide means are provided, indicated by **26** in FIG. 7, substantially constituted by rails that develop at least for part of the length of the winding element **8** and slidably receive the shaft **15** of the abrasive element **10**.

[0054] In particular, the shaft **15** is combined with rolling sliding means **27** that, cooperating with the rails **26**, guide the abrasive elements **10**, thus reducing the stress on the winding element **8** and reducing the oscillation of the winding element **8** to the minimum.

[0055] To advantage, said guide means **26** will develop for a width corresponding to the maximum width admissible for the pieces to be processed.

[0056] Combined with the sanding unit **4**, as it can be observed in detail in FIG. 2, there are pressing elements, indicated as a whole by **28**, constituted by rollers that

during the sanding process are positioned in such a way as to adhere to the piece to be processed **3** and facilitate its adhesion to the support structure **2**.

[0057] Furthermore, the support structure **2** may be provided with suction means, not represented in the figure for simplicity's sake and in any case already known, which further increase the adhesion of the piece **3**.

[0058] During operation, as shown in FIGs. **4**, **5**, and **6**, the piece to be processed **3** advances in a substantially perpendicular direction with respect to the parallel advance directions **18**, **19** of the winding element **8**.

[0059] When at the beginning of the cycle the piece **3** comes in contact with the abrasive elements **10**, as shown in detail in FIG. **4**, the laminar abrasive elements **14** of the main side **21** come in contact with the front side edge **3a** of the piece **3**, thus sanding this edge.

[0060] Successively the piece **3** advances further and, as can be observed in FIG. **5**, comes in contact with the abrasive elements **14** of both sides **20**, **21**.

[0061] In particular, the abrasive elements **14** of the side **20** come in contact with the side edge **3b** and the visible upper surface **3e** of the piece **3**.

[0062] Analogously, the abrasive elements **14** of the side **21** come in contact with the side edge **3d** and the same visible surface **3e**.

[0063] In the last sanding phase, as shown in FIG. **6**, the abrasive elements **14** of the main row **20** come in contact with the last side edge **3c** that hasn't been sanded yet, thus finishing the processing of the piece **3**.

[0064] It is clear that, independently of the shape of the piece to be sanded, all its side edges, as well as its visible surface are sanded in a single processing cycle.

[0065] It is also clear that during the processing phases the pressing elements **28**, not represented in the FIGs. from **4** to **6** for simplicity's sake, will be advantageously rested on the upper surface **3e** of the piece **3**, in order to keep it adherent to the conveyor belt **5**.

[0066] It is important to point out that, compared to the known types of sanding machines, in this case the pressing elements **28** can be arranged at a shorter distance from one another, thus ensuring optimal adhesion also for small pieces.

[0067] In case of application to more sophisticated sanding machines, a sanding unit **4** of the type described above may also be advantageously combined with traditional sanding units, for example sanding units with rotary brushes.

[0068] The FIGs. from **10** to **12** schematically show a variant of the sanding machine object of the invention during different processing phases; it differs from the previous one for the different inclination of the laminar abrasive elements **114**.

[0069] Said abrasive elements, as it can be observed, are inclined according to an alternate configuration that, compared to the previous application, ensures compensated distribution of stresses on the winding element, due to the contact of the laminar abrasive elements **114** with the piece to be processed.

[0070] In this way the oscillation of the winding element during its rotation can be further reduced and the construction of the sanding machine may be simplified, since there is no need for guide means combined with the shaft of each abrasive element.

[0071] FIG. **13** shows a further variant of the invention, which differs from the previous applications described above for the different arrangement of the laminar abrasive elements **214** that, in this case, are perpendicular to the advance directions of the winding element.

[0072] FIG. **14** shows a further variant of the invention, indicated as a whole by **300**.

[0073] It differs from the first practical application for the different construction of the support structure **302**, which in this case is constituted by a plurality of rotating rollers **305** positioned side by side which, while rotating, bring with themselves the piece to be processed that rests upon them.

[0074] Finally, FIG. **15** shows a different construction of the holding means **423** of the laminar abrasive element **414**, comprising a movable plate **424** positioned against

the laminar abrasive element **414** owing to the action of a pair of lateral springs **430** that are integral with the shaft **415**.

[0075] In this case the laminar abrasive element **414** can advantageously comprise two distinct parts **416**, **417**, the first part **416** being constituted by the abrasive paper and the second part **417** being constituted by fibrous elements.

[0076] With this configuration, maintenance operations may require the replacement of the worn abrasive paper **416** only, with no need to replace also the fibrous elements **417**.

[0077] The above clearly shows that the sanding machine object of the invention, in the different variants illustrated and described herein, achieves the aims set and offers the advantages described.

[0078] Upon implementation, further modifications that are not described and represented herein may be made on the machine object of the invention.

[0079] Said modifications may be constituted, for example, by a different position of the winding element, by a different execution of the same, for example with ring chains wound on gear wheels, or again by a different execution of the laminar abrasive elements and a different method to apply them to the winding element itself.

[0080] These and other variants, not described and not represented herein, must all be considered protected by this patent, provided that they are included in the innovative concepts expressed in the following claims.

CLAIMS

1) Sanding machine comprising:

- a support structure for supporting the piece to be processed and a frame supporting
- at least a sanding unit for processing said piece, said sanding unit comprising a winding element cooperating with kinematic means for moving it according to a closed ring configuration,

wherein said closed ring configuration of said winding element belongs to a plane substantially parallel to the plane defined by said support structure **and wherein** said winding element supports a plurality of abrasive elements spaced from one another, disposed substantially perpendicular to the plane of said support structure and defining two parallel advance directions, said abrasive elements comprising a laminar abrasive element connected with said winding element through a shaft substantially perpendicular to said plane defined by said support structure, said abrasive element being inclined with respect to the advance directions of said winding element.

2) Sanding machine according to claim 1) **wherein** said kinematic means of said winding element comprises at least two pulleys between which said winding element is wound and motorization means cooperating with at least one of said pulleys to set it rotating.

3) Sanding machine according to claim 1) **wherein** said laminar abrasive element is removably connected with said shaft through holding means.

4) Sanding machine according to claim 3) **wherein** said holding means comprise at least one moving plate suitable for being placed against the laminar abrasive element through the operation of a pawl.

5) Sanding machine according to claim 3) **wherein** said holding means comprise at least one moving plate suitable for being placed against the laminar abrasive element through the action of at least one spring integral with said shaft.

6) Sanding machine according to claim 1) **wherein** said shaft comprises articulation means suitable for defining said inclined position of said laminar abrasive element.

7) Sanding machine according to claim 1) **wherein** it comprises guide means combined with said frame, suitable for slidably receiving said shaft for at least one section during its movement.

8) Sanding machine according to claim 7) **wherein** said guide means comprise at least one track integral with said frame and are suitable for receiving rolling sliding means combined with said shaft.

9) Sanding machine according to claim 1) **wherein** said support structure can be moved with respect to said sanding unit.

10) Sanding machine according to claim 1) **wherein** said support structure comprises a conveyor belt closed to form a ring between at least one pair of rotating cylinders.

11) Sanding machine according to claim 1) **wherein** said support structure comprises a plurality of rotating rollers positioned side by side.

12) Sanding machine according to claim 1) **wherein** said sanding unit can be moved with respect to said support structure.


13) Sanding machine according to claim 1) **wherein** it comprises suction means combined with said support structure and suitable for keeping said piece adherent to said support structure.

14) Sanding machine according to claim 1) **wherein** it comprises one or more pressing elements combined with said frame, suitable for being placed in contact with said piece to keep it adherent to said support structure.

ABSTRACT


A sanding machine comprising a support structure for the piece to be processed and a sanding unit for the piece itself. The sanding unit comprises a frame that supports a winding element cooperating with kinematic means suitable for setting it in motion according to a closed ring configuration on a plane substantially parallel to the plane defined by the support structure and a plurality of abrasive elements combined with the winding element spaced from one another and provided with an abrasive surface that comes in contact with the piece during the movement of the winding element.

1/8



BEST AVAILABLE COPY

2/8



3/8










FIG.3

4/8






5/8



BEST AVAILABLE COPY

6/8



10/511330

7/8




FIG. 13





FIG. 15

BEST AVAILABLE COPY

8/8



BEST AVAILABLE COPY